



## PRODUCT DATA SHEET

TAC 2® Adhesive Chain Lubricant, 10 Wt Oz  
Part Number: 03076



|                           |   |
|---------------------------|---|
| Product Description       | An exceptional lubricant, with a tough adhesive quality which will bond to chain/wear surfaces to keep them in peak operating condition by reducing friction and wear that cause metal fatigue. |
| Applications              | Drive chains, open gears, hoists, winches, pulleys, fork lifts, rollers, garage doors, bushings, seals, o-rings, and wire ropes   |
| Unit Package Description  | 16 Ounce Aerosol  |
| Brand                     | CRC   |
| Generic Description 1     | Synthetic Lubricant   |
| Net Fill                  | 10 Wt Oz  |
| UPC Code                  | 078254030760  |
| Unit Dimensions           | 7.75H x 2.63W x 2.63D in  |
| Units Per Case            | 12  |
| Case Dimensions           | 8.1H x 8.3W x 11.1D in  |
| Cases Per Pallet          | 133   |
| Case Weight               | 11 lbs  |
| I 2 of 5 Code             | 30078254030761  |
| Appearance                | Blue Liquid   |
| Base Type                 | Hydrocarbon   |
| Flash point (F)           | <0°F  |
| Flash point (C)           | <-18°C  |
| Flammability Class - CPSC | Extremely Flammable   |
| Spec Gravity Concentrate  | 0.71  |
| Plastic Safe              | Safe on Most Plastics   |
| Film Type                 | Soft Film   |
| Film Thickness            | Not Determined  |
| Evaporation Rate          | Fast  |
| Dielectric Strength       | Not Determined  |

Last revised: 5/4/2016  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



|                            |   |
|----------------------------|---|
| Working Temp (F)           | Max 350°F                               |
| Working Temp (C)           | Max 176.7°C                             |
| Propellant                 | Hydrocarbon                             |
| NSF Category Code          | H2                                      |
| NSF Number                 | 144243                                  |
| Aerosol Flammability Level | III                                     |
| DOT Proper Shipping Name   | Aerosols, Flammable, Limited Quantity   |
| VOC % (Federal)            | 81.3                                    |
| VOC g/L (Federal)          | 577.2                                   |
| VOC Lbs./Gal. (Federal)    | 4.8                                     |
| VOC Category               | Gear, Chain or Wire Lubricant (Aerosol) |
| Restricted from Sale In:   | CA                                      |
| Removal (How To)           | Remove with Petroleum Distillates.      |

Last revised: 5/4/2016  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.