



ELECTRICAL SPECIFICATIONS

STYLE: ENCLOSED, AIR COOLED, DRY TYPE, TRANS.
 PRIMARY: - VOLTS. 60HZ.
 SECONDARY: 6000V. AT 20 MA.
 INSULATION SYSTEM: 105°C MINIMUM
 TEMPERATURE RAISE: 55°C MAXIMUM
 RATING: 175 VA.

NOTE: END OF SECONDARY GROUNDED TYPE

CAT. NO.	A06-SA6	C06-SA6
PRIM. V.	120 V.	240 V.
CYCLE	60 HZ.	60 HZ.
SEC. VA	175 VA	175 VA
SEC. V.	6000 V	6000 V
SEC. MA.	20 MA	20 MA

REV: D DRAWN ON AUTO CAD UPDATED MJ 9-19-00

REV: E PRIM WAS 120 & 240V. MJ 3-19-01

REV: C WAS AN EN-150A WITHOUT KO
ADD. EN-150 COVER W/KO 5-1-94

TITLE: OUTLINE FOR 175 VA 1PH. 60HZ.

REV: B 5.313 WAS 5.5 MJ 10-24-91

IGNITION TRANSFORMER

REV: A REDRAWN OLD PRINT 4-3-79

DONGAN ELECTRIC
 MFG. CO.
 PIONEER TRANSFORMER CO.

TOLERANCES
 DECIMAL DIMENSIONS ±.030
 FRACTIONAL DIMENSIONS ±1/32

SCALE:
 3D

MADE BY
 JAL

DATE
 4-3-79

CHECKED & APPROVED

PART NUMBER
 A06-SA6
 C06-SA6

DRAWING NUMBER
 10-366