



Ultra Lite 3-36® Ultra Thin Non Staining Lubricant, 11 Wt Oz No. 03160 | Item# 1003427 | Case# 1003426

Product Description

Ultra-thin, non-staining lubricant that resists oil, dirt and dust build-up. Seals out moisture and prevents corrosion with protective film. Excellent for drying out electrical/electronic components.

Applications

Locks, latches, hinges, gauges, taps, dies, fixtures, fans, precision metal processing equipment, metal plating, coin mechanisms, solid work surfaces, clips, springs, control buttons, switches, bushings, window slides and rollers.

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

Ultra Thin Non Staining Lubricant

Net Fill

11 Wt Oz

UPC Code

078254031606

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.1H x 8.3W x 11.1D in

Cases Per Pallet

133

Case Weight

12 lbs

I 2 of 5 Code

30078254031607

Appearance

Amber Liquid

Base Type

Petroleum Solvent

Flash point (F)

172°F

Flash point (C)

78°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.8034

Plastic Safe

No

Film Type

Ultra Thin and Dry

Film Thickness

0.05 Mils

Evaporation Rate

Slow

Dielectric Strength

37,600 Volts

Last revised: 7/30/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (F)	-40 to 300°F
Working Temp (C)	-40 to 148.9°C
Propellant	Carbon Dioxide
NSF Category Code	H2
NSF Number	017425
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	43.8
VOC g/L (Consumer Product def)	351.9
VOC lbs/gal (Consumer Prod def)	2.9
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

Last revised: 7/30/2019
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.