

# ALTERNATIVE / MARINE / FUEL

## SS25UL

### Markets



- Low-pressure service with liquefied petroleum gas
- UL Standard 21 certification
- Oil and LPG resistant synthetic fiber cover
- Compatible with 26 Series Parkrimp style fittings

### SS25UL

Transportation – Liquefied Petroleum Gas  
UL 21 / NFPA 58



[view on web page](#)

| #<br>Part Number | Hose I.D. |      | Hose O.D. |      | Working Pressure |     | Minimum Bend Radius |    | Weight |      | Parkrimp<br>26 Series | Field<br>Attachable<br>20/22 Series |
|------------------|-----------|------|-----------|------|------------------|-----|---------------------|----|--------|------|-----------------------|-------------------------------------|
|                  | inch      | mm   | inch      | mm   | psi              | MPa | inch                | mm | lbs/ft | kg/m |                       |                                     |
| SS25UL-4         | 3/16      | 5    | 0.52      | 13,2 | 350              | 2,4 | 0.75                | 20 | 0.11   | 0,16 | •                     | •                                   |
| SS25UL-5         | 1/4       | 6,3  | 0.58      | 14,8 | 350              | 2,4 | 1                   | 25 | 0.13   | 0,19 | •                     | •                                   |
| SS25UL-6         | 5/16      | 8    | 0.68      | 17,2 | 350              | 2,4 | 1-1/4               | 30 | 0.18   | 0,27 | •                     | •                                   |
| SS25UL-8         | 13/32     | 10   | 0.77      | 19,5 | 350              | 2,4 | 1-3/4               | 45 | 0.21   | 0,31 | •                     | •                                   |
| SS25UL-10        | 1/2       | 12,5 | 0.92      | 23,4 | 350              | 2,4 | 2-1/4               | 55 | 0.29   | 0,43 | •                     | •                                   |
| SS25UL-12        | 5/8       | 16   | 1.08      | 27,4 | 350              | 2,4 | 2-3/4               | 70 | 0.37   | 0,55 | •                     | •                                   |

**Application:** Liquefied petroleum gas (LPG).

**Inner Tube:** Synthetic rubber.

**Reinforcement:** One fiber braid and one stainless steel wire braid.

**Cover:** Fiber braid.

**Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**Fittings:** 26 Series - pg. B-9.  
20 Series - pg. B-149.  
22 Series - pg. B-165.

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

### SS25UL-AGA

Transportation – Liquefied Petroleum Gas  
AS / NZS 1869-2012 CLASS D



[view on web page](#)

| #<br>Part Number | Hose I.D. |    | Hose O.D. |      | Working Pressure |     | Minimum Bend Radius |    | Weight |      | Parkrimp<br>26 Series | Field<br>Attachable<br>20/22 Series |
|------------------|-----------|----|-----------|------|------------------|-----|---------------------|----|--------|------|-----------------------|-------------------------------------|
|                  | inch      | mm | inch      | mm   | psi              | MPa | inch                | mm | lbs/ft | kg/m |                       |                                     |
| SS25UL-4-AGA     | 3/16      | 5  | 0.52      | 13,2 | 375              | 2,6 | 0.75                | 20 | 0.11   | 0,16 | •                     | •                                   |
| SS25UL-6-AGA     | 5/16      | 8  | 0.68      | 17,2 | 375              | 2,6 | 1-1/4               | 30 | 0.18   | 0,27 | •                     | •                                   |
| SS25UL-8-AGA     | 13/32     | 10 | 0.77      | 19,5 | 375              | 2,6 | 1-3/4               | 45 | 0.21   | 0,31 | •                     | •                                   |

FACTORY MADE HOSE ASSEMBLIES ONLY. Contact Hose Products Division for more information.

**Application:** Liquefied petroleum gas (LPG).

**Inner Tube:** Synthetic rubber.

**Reinforcement:** One fiber braid and one stainless steel wire braid.

**Cover:** Fiber braid.

**Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**Fittings:** 26 Series - pg. B-9.  
20 Series - pg. B-149.  
22 Series - pg. B-165.

- See Section B for Field Attachable Assembly Instructions.
- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).